



## ALFRIMAL® 445 LV for plastics & resins

### LOW VISCOSITY AND HIGH FILLING RATE

Halogen-free filler generation based on aluminum hydroxide, which is especially suitable as flame retardant for plastics and resin-based articles. The particle size distribution of this product is optimized for applications in all kind of resins, creating low viscosity (LV).

#### Applications

##### Building panels:

- Higher filling grades of polymers
- Reduced smoke development

##### Plastic structural elements:

- High quality compounds
- Special FR for different applications

##### Hard components:

- Standard FR for all common products



#### Key benefits

- Fine particle-sized ATH
- Acts as HFFR
- Low viscosity behavior ("LV")
- High filling of resins
- Improved processability of filled materials
- Reduced shear
- Independent on pH

Product	Color	D <sub>50</sub>
ALFRIMAL® 445 LV	white	11 µm



For more information please scan the QR code or contact our sales department:

Phone: +49 2236 8914 20 E-Mail: [info@alpha-calcit.de](mailto:info@alpha-calcit.de)

01-KS-22

**Alpha Calcit Füllstoff Gesellschaft mbH & Co. KG**

Otto-Hahn-Str. 9-11 - 50997 Cologne-Godorf (Germany)

homepage: [www.alpha-calcit.de](http://www.alpha-calcit.de)

